

Universal Contractor Grade Pads

GP-H HeavyWeight,15" W x 18" L,100 pads per package

Part of making smart spill decisions is not buying more absorbent than you need. Not every job requires long-term durability or heavy-duty strength. Sometimes you need an absorbent that will let you get in, do the job, and get out.

- Universal absorbency - used for both oil-and water-based liquids
- Perforations allow you to use only what you need
- Dimples add fast-wicking power
- Quickly absorbs leaks, spills and overspray to keep floors dry
- Perfect for light-duty industrial, maintenance and general applications
- Pads are ideal for catching leaks and soaking up spills
- HighLoft construction is sturdy and soft

Specifications

Shipping Dimensions	15" W x 18" L x 12" H
Ship Class	175
Dimensions	15" W x 18" L
Mat Weight	HeavyWeight
Absorbency	Up to 22 gal. per pkg
Absorbency per	Up to 28.2 oz. per pad
Absorbency Range	20 - 29.9 gal.
Fluid Absorbed	Oils; Coolants; Solvents; Water; Universal
Incinerable	Yes
Perforated	Yes
Perforated Pattern	7.5" W x 19" L sections
Static-Dissipative	No
Sold As	100 pads per package
Weight	9 lbs.
# per Pallet	42
Composition	Polypropylene
UNSPSC	47131901

Color	Gray

Technical Information

Technical Documents

SpillTech Compatibility

Safety Data Sheet (SDS) for 100% Polypropylene Absorbents

Tech Spec for Universal Contractor Grade

29 CFR 1910.107(b)(3)

29 CFR 1910.107(g)(2)

29 CFR 1910.120(j)(1)

29 CFR 1910.1450(e)

29 CFR 1910.22(a)(2)

49 CFR 173.3(c)(2)

SpillTech
Smart Spill Solutions™

6455 East Johns Crossing, Suite 375 • Johns Creek, GA 30097 USA

Phone: 1-800-228-3877 (In North America)
Phone: 1-770-475-3877 (Outside North America)
Fax: 1-800-872-3764 (In North America)
Fax: 1-770-410-1812 (Outside North America)